



Ultracoat Hard Oil Hardener

Admixture specific to promote hardening of Ultracoat Hard Oil Fast

CHARACTERISTICS

Ultracoat Hard Oil Hardener promotes quicker curing of the **Ultracoat Hard Oil Fast**, increases its surface hardness and improves the finishing product's resistance to stains.

Preparation of the product

Pour **Ultracoat Hard Oil Hardener** into the container of **Ultracoat Hard Oil Fast** and mix thoroughly. Pour the mix obtained into a clean container, making sure that no residues remain, especially residues of colour. Mix again for 3 minutes.

Ultracoat Hard Oil Fast can be applied as described in the relevant Technical Data Sheet.

PACKAGING

6x100 g bottles.

STORAGE

12 months in sealed packaging, stored at a temperature between +10°C and +30°C.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Ultracoat Hard Oil Hardener can cause sensitization if it comes in contact with the skin of those sensitive to isocyanates, it is irritant for the eyes and the respiratory tract. Furthermore, it is harmful if inhaled. During use wear protective gloves and goggles and to take the usual precautions for handling chemicals. If the product comes in contact

with the eyes or skin wash immediately with plenty of water and seek medical attention. Use a suitable device for protecting the respiratory tract.

Ultracoat Hard Oil Hardener is dangerous for aquatic life, do not dispose of it in the environment. For further and complete information about the safe use of our product please refer to the latest version of our Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the **Technical Data Sheet**, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related

Ultracoat Hard Oil Hardener

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

| | |
|----------------------|--------------------------|
| Consistency: | thick liquid |
| Colour: | transparent |
| Odour: | own characteristic odour |
| Solubility in water: | partially soluble |
| Density: | 1 kg/litre |

document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation. The most up-to-date TDS can be downloaded from our website www.mapei.com. ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR

DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

4641-7-2019 (GB)



BUILDING THE FUTURE